


Lightweight roofing solutions for a lifetime



M - - PA



Units in mm



415

Design

The MISTRAL is designed to create an elegant and undulating form that is typical for West-European houses.

MISTRAL is a stone-coated panel pressed from a high grade of Zinc-Aluminium or equivalent coated steel and is available in a wide selection of colours to enhance any exterior colour scheme.

Installation

The roof panels can be interlocked either rightover left or left over right with the side laps of one small corrugation.

The panels are placed onto battens spacing 370 mm.

The downturned front edge and the upturned rear edge of eachtile provides a strong, weatherproof, overlapping and interlockingroof covering. Each tile is secured into the top of the batten by 4 nails or screws in the upturned rear edge. The tile is also secured to the next tile by 4 nails or screws in the frontdownturned edge, positioned out of the water course.

Specifications

Minimum pitch	10°
Maximum pitch	90°
Size of tile - overall*	1305 x 415 mm [± 3 mm]
Size of tile - cover*	1240 x 370 mm
Gauge of steel	0,45 mm
Linear cover width*	1240 mm
Coverage*	0,46 m ² (2,18 tiles per m ²)
Weight per m ² **	6,5 kg
Weight per tile **	3,0 kg
weight per the	3,0 Kg

The measurements and the weight may vary slightly by the finish that is added to the accessory.
** Steel thickness according to the EN 10346.

Packing

Pieces per pallet	360
Pallet composition	18 stacks of 20 pieces
Pallet dimensions	1400 x 1100 mm x 800 mm